

## ASHBY

### TOP CONSTRUCTION

- SUBSTRATE:** Standard table tops are constructed with 1-1/8" M3 Industrial Grade 47# density particle board. NAUF and FSC® options are available.
- DECORATIVE SURFACE:** Constructed with HPL (high pressure laminate) which meets or exceeds performance requirements of NEMA LD 3
- BACKER:** Backer matched grade of laminate for balanced construction. Meets or exceeds performance requirements of NEMA LD 3
- ADHESIVE:** GREENGUARD® Certified Water-Based PVA glue
- EDGING:** See edge treatment guide for more information on edging options [www.surfaceworks.us/Edges.html](http://www.surfaceworks.us/Edges.html)
- MOUNTING:** Table tops are predrilled for easy installation & alignment.



### BASE CONSTRUCTION

- DESCRIPTION:** Welded top plate for strength and durability
- MATERIAL:** Tubing: Column - 2" dia. 14 gauge steel
- FINISH:** Powder coated with scuff resistant environmentally friendly powder
- HEIGHT:** 27.75"
- FOOT TYPE (STANDARD):** (1) 1/4-20 glides
- FOOT TYPE (OPTIONAL):** Casters- 2" dual wheel locking
- MOUNTING PLATE:** 6" x 6" 7 gauge steel