



06.05.2017 Rev. A

1

ARCHES

TOP CONSTRUCTION

SUBSTRATE: Standard table tops are constructed with 1-1/8" M3

Industrial Grade 47# density particle board. NAUF and

FSC® options are available.

DECORATIVE Constructed with HPL (high pressure laminate) which meets SURFACE:

or exceeds performance requirements of NEMA LD 3

BACKER: Backer matched grade of laminate for balanced

construction. Meets or exceeds performance requirements

of NEMA LD 3

ADHESIVE: GREENGUARD® Certified Water-Based PVA glue

EDGING: See edge treatment guide for more information on edging

options www.surfaceworks.us/Edges.html

MOUNTING: Table tops are predrilled for easy installation & alignment.





BASE CONSTRUCTION

DESCRIPTION: Rigid bolted/welded base for superior strength and

durability

Tubing: Column 3" OD x 16 gauge. Base 1 3/8" OD **MATERIAL**:

x13 gauge

FINISH: Powder coated with scuff resistant enviormentally

friendly powder

HEIGHT: 27.75" (Seated)

40.75" (Pub)

FOOT TYPE 1-3/8" diameter and 1/4-20 x 5/8" long stud

(STANDARD):

FOOT TYPE (OPTIONAL): Casters- 2" dual wheel locking

MOUNTING **PLATE:**

8" x 8" x 1/4" Fabricated steel

06.05.2017 Rev. A

ARCHES FLIP-TOP

TOP CONSTRUCTION

SUBSTRATE: Standard table tops are constructed with 1-1/8" M3

Industrial Grade 47# density particle board. NAUF and FSC

options are available.

DECORATIVE Constructed with HPL (high pressure laminate) which meets

SURFACE: or exceeds performance requirements of NEMA LD 3

BACKER: Backer matched grade of laminate for balanced

construction. Meets or exceeds performance requirements

of NEMA LD 3

ADHESIVE: GREENGUARD® Certified Water-Based PVA glue

EDGING: See edge treatment guide for more information on edging

options www.surfaceworks.us/Edges.html

MOUNTING: Table tops are predrilled for easy installation & alignment.





BASE CONSTRUCTION

DESCRIPTION: Rigid bolted/welded base for superior strength and

durability with integrated flip-top mechanism

MATERIAL: Tubing: Column 3" OD x 16 gauge. Base 1 3/8" OD

x13 gauge

FINISH: Powder coated with scuff resistant enviormentally

friendly powder

HEIGHT: 27.75"

FOOT TYPE 1-3/8" diameter and 1/4-20 x 5/8" long stud

(STANDARD):

FOOT TYPE Casters- 2" dual wheel locking

(OPTIONAL):

F 414.570.2676

P 414.570.2677