06.05.2017 Rev. A

1

## **BEHEMOTH ADJUSTABLE**

## TOP CONSTRUCTION

SUBSTRATE: Standard table tops are constructed with 1-1/8" M3

Industrial Grade 47# density particle board. NAUF and

FSC® options are available.

**DECORATIVE** Constructed with HPL (high pressure laminate) which meets

**SURFACE:** or exceeds performance requirements of NEMA LD 3

**BACKER:** Backer matched grade of laminate for balanced

construction. Meets or exceeds performance requirements

of NEMA LD 3

ADHESIVE: GREENGUARD® Certified Water-Based PVA glue

**EDGING:** See edge treatment guide for more information on edging

options www.surfaceworks.us/Edges.html

MOUNTING: Table tops are predrilled for easy installation & alignment.





### **BASE CONSTRUCTION**

**DESCRIPTION:** Rigid bolted/welded post leg base with full under-

surface frame for superior strength and durability with set-screw height adjustable lower legs.

MATERIAL: Tubing: Mounting Frame- 1"x2" 14-gauge steel.

Legs- 1-1/4"x 1-1/4" 14-gauge steel

FINISH: Powder coated with scuff resistant enviormentally

friendly powder

**HEIGHT:** 20.75" (min)

28.75" (max)

FOOT TYPE

(STANDARD):

(4) steel glides

MOUNTING PLATE:

Full size frame with 6-12 mounting points



06.05.2017 Rev. A

# **BEHEMOTH FIXED**

## **TOP CONSTRUCTION**

SUBSTRATE: Standard table tops are constructed with 1-1/8" M3

Industrial Grade 47# density particle board. NAUF and FSC

options are available.

**DECORATIVE** Constructed with HPL (high pressure laminate) which meets SURFACE:

or exceeds performance requirements of NEMA LD 3

**BACKER:** Backer matched grade of laminate for balanced

construction. Meets or exceeds performance requirements

of NEMA LD 3

ADHESIVE: GREENGUARD® Certified Water-Based PVA glue

**EDGING:** See edge treatment guide for more information on edging

options www.surfaceworks.us/Edges.html

**MOUNTING:** Table tops are predrilled for easy installation & alignment.





### **BASE CONSTRUCTION**

**DESCRIPTION:** Rigid bolted/welded post leg base with full under-

surface frame for superior strength and durability.

Tubing: Mounting Frame- 1"x2" 14-gauge steel. **MATERIAL**:

Legs- 1-1/4"x 1-1/4" 14-gauge steel

FINISH: Powder coated with scuff resistant enviormentally

friendly powder

**HEIGHT:** 27.75"

**FOOT TYPE** (4) steel glides

(STANDARD):

**MOUNTING** 

**PLATE:** 

Full size frame with 6-12 mounting points