

06.05.2017 Rev. A

# **ELEMENTS**

## TOP CONSTRUCTION

SUBSTRATE: Standard table tops are constructed with 1-1/8" M3

Industrial Grade 47# density particle board. NAUF and

FSC® options are available.

**DECORATIVE** Constructed with HPL (high pressure laminate) which meets SURFACE:

or exceeds performance requirements of NEMA LD 3

**BACKER:** Backer matched grade of laminate for balanced

construction. Meets or exceeds performance requirements

of NEMA LD 3

ADHESIVE: GREENGUARD® Certified Water-Based PVA glue

**EDGING:** See edge treatment guide for more information on edging

options www.surfaceworks.us/Edges.html

**MOUNTING:** Table tops are predrilled for easy installation & alignment.





### **BASE CONSTRUCTION**

**DESCRIPTION:** All welded base for maximum strength and durability

Tubing: Column - 2" 14 gauge Steel. Foot:2" 14 **MATERIAL:** 

gauge Steel with welded Steel end cap and welded

Steel insert for Glides.

FINISH: Powder coated with scuff resistant environmentally

friendly powder

**HEIGHT:** 27.75"

**FOOT TYPE** 1-3/8" diameter and 5/16"-18 stud w/ nylon foot

(STANDARD):

**FOOT TYPE** Casters- 2" dual wheel locking

(OPTIONAL):

Heavy duty Welded Steel - .175"x 6"x 8"

**MOUNTING** 

06.05.2017 Rev. A

# **ELEMENTS FOLDING**

## **TOP CONSTRUCTION**

SUBSTRATE: Standard table tops are constructed with 1-1/8" M3

Industrial Grade 47# density particle board. NAUF and FSC

options are available.

**DECORATIVE** Constructed with HPL (high pressure laminate) which meets SURFACE:

or exceeds performance requirements of NEMA LD 3

**BACKER:** Backer matched grade of laminate for balanced

construction. Meets or exceeds performance requirements

of NEMA LD 3

**ADHESIVE:** GREENGUARD® Certified Water-Based PVA glue

**EDGING:** See edge treatment guide for more information on edging

options www.surfaceworks.us/Edges.html

**MOUNTING:** Table tops are predrilled for easy installation & alignment.





### **BASE CONSTRUCTION**

**DESCRIPTION:** Welded/bolted base for strength and durability with

integrated folding mechanism

14 gauge, 2" diameter tubular steel T-leg with **MATERIAL:** 

welded end caps

FINISH: Powder coated with scuff resistant environmentally

friendly powder

**HEIGHT:** 27.75"

**FOOT TYPE** 1-3/8" diameter and 5/16"-18 stud w/ nylon foot

(STANDARD):

Casters- 2" dual wheel locking

**FOOT TYPE** (OPTIONAL):

**MOUNTING** Molded plastic with steel spring clip. Legs lock in at

PLATE: both opened and closed position.

F 414.570.2676

P 414.570.2677