

10.02.2019 Rev. A

JAMESTOWN

TOP CONSTRUCTION

SUBSTRATE:	Standard table tops are constructed with 1-1/8" M3 Industrial Grade 47# density particle board. NAUF and FSC options are available.
DECORATIVE SURFACE:	Constructed with HPL (high pressure laminate) which meets or exceeds performance requirements of NEMA LD 3
BACKER:	Backer matched grade of laminate for balanced construction. Meets or exceeds performance requirements of NEMA LD 3
ADHESIVE:	GREENGUARD® Certified Water-Based PVA glue
EDGING:	See edge treatment guide for more information on edging options www.surfaceworks.us/Edges.html
MOUNTING:	Table tops are predrilled for easy installation & alignment.





BASE CONSTRUCTION

DESCRIPTION:	Rigid bolted cast iron base for superior strength and durability
MATERIAL:	Column: Cast Iron, Base: Cast Iron, Tie Rod: 1/2"-13 threaded rod
FINISH:	Powder coated with scuff resistant enviormentally friendly powder
TABLE HEIGHT: (WITH TOP)	Approximate height +/5 variance 29.75"
FOOT TYPE	(4) 1/4-20 glides

(STANDARD):

MOUNTING 7-5/8" stamped steel or 11"cast iron spider bracket PLATE: