



06.05.2017 Rev. A

1

JEFFERSON

TOP CONSTRUCTION

SUBSTRATE: Standard table tops are constructed with 1-1/8" M3

Industrial Grade 47# density particle board. NAUF and

FSC® options are available.

Constructed with HPL (high pressure laminate) which meets DECORATIVE SURFACE:

or exceeds performance requirements of NEMA LD 3

BACKER: Backer matched grade of laminate for balanced

construction. Meets or exceeds performance requirements

of NEMA LD 3

ADHESIVE: GREENGUARD® Certified Water-Based PVA glue

EDGING: See edge treatment guide for more information on edging

options www.surfaceworks.us/Edges.html

MOUNTING: Table tops are predrilled for easy installation & alignment.



BASE CONSTRUCTION

DESCRIPTION:

Fiberboard cube with rounded corners, 3/8" wall thickness. Laminated w/HPL. 3/4" particle board ring

at top and bottom for structure and stability

MATERIAL:

Laminated fiberboard cylinder, 3/8" wall thickness

and 3/4" particle board ring at top and bottom for

structure and stability

FINISH:

HEIGHT:

FOOT TYPE

(STANDARD):

FOOT TYPE (OPTIONAL):FO **OT TYPE**

(STANDARD):

MOUNTING PLATE: MOUNTI

N):

Wire Access Panel

(4) 4"x 6" hardwood cleats per base