

06.05.2017 Rev. A

STATIC

TOP CONSTRUCTION

SUBSTRATE: Standard table tops are constructed with 1-1/8" M3

Industrial Grade 47# density particle board. NAUF and

FSC® options are available.

DECORATIVE Constructed with HPL (high pressure laminate) which meets SURFACE:

or exceeds performance requirements of NEMA LD 3

BACKER: Backer matched grade of laminate for balanced

construction. Meets or exceeds performance requirements

of NEMA LD 3

ADHESIVE: GREENGUARD® Certified Water-Based PVA glue

EDGING: See edge treatment guide for more information on edging

options www.surfaceworks.us/Edges.html

MOUNTING: Table tops are predrilled for easy installation & alignment.





BASE CONSTRUCTION

DESCRIPTION: Rigid bolted/welded base for superior strength and

durability

Tubing: Column - Aluminum extrusion. Base - steel, **MATERIAL**:

molded ABS end caps

FINISH: Powder coated with scuff resistant enviormentally

friendly powder

HEIGHT: 27.75"

FOOT TYPE 3/8-16x .87" long shank, 1.87" dia.

(STANDARD):

FOOT TYPE Casters- 2" dual wheel locking

(OPTIONAL):

MOUNTING PLATE: 13/16"x 6"x 8" steel