

06.05.2017 Rev. A

T-FACTO 2 POST T-LEG

TOP CONSTRUCTION

SUBSTRATE:	Standard table tops are constructed with 1-1/8" M3 Industrial Grade 47# density particle board. NAUF and FSC® options are available.
DECORATIVE SURFACE:	Constructed with HPL (high pressure laminate) which meets or exceeds performance requirements of NEMA LD 3
BACKER:	Backer matched grade of laminate for balanced construction. Meets or exceeds performance requirements of NEMA LD 3
ADHESIVE:	GREENGUARD® Certified Water-Based PVA glue
EDGING:	See edge treatment guide for more information on edging options www.surfaceworks.us/Edges.html
MOUNTING:	Table tops are predrilled for easy installation & alignment.



BASE CONSTRUCTION

(STANDARD): leg



DESCRIPTION:	Rigid bolted, tubular, dual-column T-Leg base for superior strength and durability
MATERIAL:	Tubing: Columns - 2" dia. 14 gauge steel. Base - 14 gauge steel
FINISH:	Powder coated with scuff resistant enviormentally friendly powder
HEIGHT:	27.75"
FOOT TYPE	(2) 1-3/8" diameter 5/8" long stud w/8mm thread per

MOUNTING 6"x 12"x 1/4" or 6"x 16"x 1/4" depending on base PLATE: spread



PRODUCT SPEC SHEET T-FACTO

> 06.05.2017 Rev. A

T-FACTO 4 POST X-BASE

TOP CONSTRUCTION

SUBSTRATE:	Standard table tops are constructed with 1-1/8" M3 Industrial Grade 47# density particle board. NAUF and FSC® options are available.
DECORATIVE SURFACE:	Constructed with HPL (high pressure laminate) which meets or exceeds performance requirements of NEMA LD 3
BACKER:	Backer matched grade of laminate for balanced construction. Meets or exceeds performance requirements of NEMA LD 3
ADHESIVE:	GREENGUARD® Certified Water-Based PVA glue
EDGING:	See edge treatment guide for more information on edging options www.surfaceworks.us/Edges.html
MOUNTING:	Table tops are predrilled for easy installation & alignment.



BASE CONSTRUCTION

\langle	THI	
G		

DESCRIPTION:	Rigid bolted, tubular, four-column X-base for superior strength and durability
MATERIAL:	Tubing: Columns - 2" dia. 14 gauge steel. Base - 14 gauge steel
FINISH:	Powder coated with scuff resistant enviormentally friendly powder
HEIGHT:	27.75"

FOOT TYPE (STANDARD):	(4) 1-3/8" diameter 5/8" long stud w/8mm thread per base
FOOT TYPE (OPTIONAL):	Casters- 2" dual wheel locking
MOUNTING PLATE:	6"x 12"x 1/4" or 6"x 16"x 1/4" depending on base spread